



**DIRECT AC  
DRIVERLESS**

**EMI  
SILENT**



## DIRECT-AC TUNNEL LIGHTING FIXTURE

### Product Features

#### Replacable IP68 LED Module

Permanently sealed IP68 LED module with waterproof quick disconnect and latching clips for fast replacement - no tools required.

#### Long Lifetime Direct-AC Driverless, EMI Silent

Uses modern direct-AC technology to drive LED strings directly from AC line voltage, without a traditional LED driver for extreme reliability and low RF emissions. Compliant to MIL-STD-461E RE102 EMI testing.

#### Integrated Wiring Box

Easily terminate any of the various wiring types used in today's tunnel environment.

#### Buy America Compliant

Engineered and manufactured in New York and Buy America compliant, G&G's RTX fixture is built on quality, innovation, and the latest in LED technology.

### Performance Summary

**Delivered Light Output:** Up to 10,000 Lumens

**Efficacy:** Up to 120 LPW

**CRI:** Typical 85 CRI

**CCT:** 4000K & 5000K (other CCT available upon inquiry)

**Lifetime:** 100,000 Hour L70 at 25°C

**Warranty:** 5 Years (See ggled.net for Terms)

**Mounting:** Wall, Rack Mount

**Protection Class:** IP66/68

**Voltage:** 120, 277, 347V Input

## Ordering Information

Contact factory for emergency lighting options, alternate lengths, outputs, color temperatures, etc.

Product	Length	Color Temp.	Voltage
RTX	4 4-Foot	50K (standard) 5000 Kelvin	120V 120 VAC Input
		40K 4000 Kelvin	277V 277 VAC Input
			347V 347 VAC Input

## DIRECT-AC TUNNEL LIGHTING FIXTURE

### Product Specifications

#### Construction & Materials

Built-in wiring box. 3/4" NPT hubs.  
 Integrated aluminum heat spreader.  
 Anodized aluminum fixture body.

Seamless polymeric outer shell provides IP68 ingress protection and is specialized for superior chemical resistance. An additional protective coating is available which integrates a UV inhibitor and UV blocker for outdoor applications.

All G&G luminaires and components (with the exception of our LED boards and drivers) are proudly manufactured and assembled in the USA.

#### Regulatory Qualifications

cULus Listed  
 UL Listed for Wet Locations  
 NEMA 4X Rated  
 NFPA 130  
 NFPA 502

### Lumen & Power Data

Model	Lumens	Wattage	Amps @120V	Amps @277V	Amps @347V
RTX4	5,000	42	0.35	0.16	0.13

### Dimensions

